

App. No. 10/608,725
Amdt. Dated May 26, 2006
Reply to Office Action of February 28, 2006
Atty. Dkt. No. 9129-109

IN THE CLAIMS:

This listing of claims will replace all prior versions, and listings of claims in the application:

1. (Previously Amended) A magnetoencephalography system, comprising:
a portable cart for moving along the ground;
a SQUID dewar containing liquid helium mounted in an inverted manner on the cart;
a headrest assembly mounted on the cart and having a headrest with a honeycomb supporting structure for supporting a head of a patient and forming a portion of the dewar;
the headrest assembly includes an array of magnetic sensors of the SQUID dewar for responding to electrical activity of the brain of the head, the sensors at least partially disposed within the honeycomb structure; and
a patient bed mounted on the cart adjacent to the headrest for supporting the body of the patient with his or her head supported by the headrest.
2. (Original) A magnetoencephalography system according to claim 1, wherein said headrest is concave and is configured in an ellipsoid shape having a sagittal radius of curvature of between about 80 millimeters and about 120 millimeters for the sagittal axis of the head and having a coronal radius of curvature of between about 60 millimeters and about 90 millimeters at the coronal axis of the head.

App. No. 10/608,725
Amdt. Dated May 26, 2006
Reply to Office Action of February 28, 2006
Atty. Dkt. No. 9129-109

3. (Original) A magnetoencephalography system according to claim 2, wherein the sagittal radius is between about 90 millimeters and about 110 millimeters, and wherein the coronal radius is between about 70 millimeters and about 80 millimeters.

4. (Original) A magnetoencephalography system according to claim 3, wherein said sagittal radius is about 100 millimeters, and wherein the coronal radius is about 75 millimeters.

5. (Original) A magnetoencephalography system according to claim 1, wherein the headrest is composed of non-metallic head-insulating structurally strong material.

6. (Original) A magnetoencephalography system according to claim 5, wherein said material is G-10 fiberglass.

7. (Original) A magnetoencephalography system according to claim 1, wherein each one of said sensors is disposed at a spacing distance from the outer head engaging surface of between about one millimeter and about three millimeters.

8. (Original) A magnetoencephalography system according to claim 7, wherein said spacing distance is between about one millimeter and about two millimeters.

9. (Original) A magnetoencephalography system according to claim 1, wherein each one of said sensors is disposed at a spacing distance of greater than about one millimeter from the outer head engaging surface of the headrest assembly.

App. No. 10/608,725
Amdt. Dated May 26, 2006
Reply to Office Action of February 28, 2006
Atty. Dkt. No. 9129-109

10. (Original) A magnetoencephalography system according to claim 1, wherein each one of said sensors is a superconducting gradiometer having a pick-up coil diameter of between about four millimeters and about eight millimeters.

11. (Original) A magnetoencephalography system according to claim 10, wherein said pick-up coil diameter of between about five millimeters and about seven millimeters.

12. (Original) A magnetoencephalography system according to claim 11, wherein said pick-up diameter is about six millimeters.

13. (Original) A magnetoencephalography system according to claim 1, wherein each one of said sensors is a superconducting gradiometer having a pick-up coil, said sensors being substantially uniformly distributed relative to the head engageable surface of the headrest, each one of the sensor pick-up coils being spaced apart by a spacing distance of between about 6 millimeters and about 14 millimeters.

14. (Original) A magnetoencephalography system according to claim 13, wherein said spacing distance is between about 8 millimeters and about 12 millimeters.

15. (Original) A magnetoencephalography system according to claim 13, wherein said sensors are arranged in groups of four, wherein the spacing distance between adjacent sensors of a group is about 8.5 millimeters and the spacing distance between diagonally disposed sensors of a group is about 12 millimeters.

16. (Original) A magnetoencephalography system according to claim 1, wherein said sensors are arranged in groups thereof, and wherein said headrest has a

App. No. 10/608,725
Amdt. Dated May 26, 2006
Reply to Office Action of February 28, 2006
Atty. Dkt. No. 9129-109

corresponding series of recesses in the rear surface thereof positioned opposite to said groups of said sensors.

17. (Original) A magnetoencephalography system according to claim 16, wherein each one of said recesses is dimensioned to the approximate size of its group of sensors.

18. (Currently Amended) A magnetoencephalography system according to claim 17, wherein said recesses are arranged in a the honeycomb structure of the headrest configuration.

19. (Original) A magnetoencephalography system according to claim 18, wherein each one of said group comprises four sensors.

20. (Original) A magnetoencephalography system according to claim 1, wherein said sensors are arranged in groups of four, each one of said four sensors of a group provides a separate communication channel, the channels being useable individually, or combined or subtracted.

21. (Original) A magnetoencephalography system according to claim 1, wherein said cart includes electronic equipment for data acquisition from said sensors, and further including a container composed of conductive material for confining said electronic equipment to shield it from radio frequency interference.

22. (Original) A magnetoencephalography system according to claim 21, wherein said dewar has an external coating of conductive material for radio frequency interference shielding.

App. No. 10/608,725
Amdt. Dated May 26, 2006
Reply to Office Action of February 28, 2006
Atty. Dkt. No. 9129-109

23. (Original) A magnetoencephalography system according to claim 21, further including a direct current power supply for supplying electrical power to said electronic equipment.

24. (Original) A magnetoencephalography system according to claim 23, further including a trailer having said power supply mounted thereon and being connected mechanically to said cart.

25. (Currently Amended) A ~~headrest assembly for a~~
~~magnetoencephalography system, comprising:~~ magnetoencephalography system
according to claim 1.

~~a concave headrest assembly having a headrest for supporting a head of~~
~~a patient;~~

wherein said array is an array of closely-spaced evenly-distributed
cryocooled superconducting sensors disposed adjacent to the headrest for responding
to electrical activity of the brain of the head, the sensors are cryocooled using liquid
helium; ~~and~~

~~said headrest being configured in an ellipsoid shape having a sagittal~~
~~radius of curvature of between about 80 millimeters and about 100 millimeters for the~~
~~sagittal axis of the head, having a coronal radius of curvature of between about 60~~
~~millimeters and about 90 millimeters at the coronal axis of the head, and having a~~
~~honeycomb supporting structure in which the sensors are at least partially disposed.~~

App. No. 10/608,725
Amdt. Dated May 26, 2006
Reply to Office Action of February 28, 2006
Atty. Dkt. No. 9129-109

26. (Canceled) A headrest assembly according to claim 25, wherein said headrest is concave and is configured in an ellipsoid shape having a sagittal radius of curvature of between about 80 millimeters and about 120 millimeters for the sagittal axis of the head and having a coronal radius of curvature of between about 60 millimeters and about 90 millimeters at the coronal axis of the head.

27. (Canceled) A headrest assembly according to claim 26, wherein the sagittal radius is between about 90 millimeters and about 110 millimeters, and wherein the coronal radius is between about 70 millimeters and about 80 millimeters.

28. (Canceled) A headrest assembly according to claim 27, wherein said sagittal radius is about 100 millimeters, and wherein the coronal radius is about 75 millimeters.

29. (Canceled) A headrest assembly according to claim 25, wherein the headrest is composed of non-metallic head-insulating structurally strong material.

30. (Canceled) A headrest assembly according to claim 29, wherein said material is G-10 fiberglass.

31. (Canceled) A headrest assembly according to claim 25, wherein each one of said sensors is disposed at a spacing distance from the outer head engaging surface of between about one millimeter and about three millimeters.

32. (Canceled) A headrest assembly according to claim 31, wherein said spacing distance is between about one millimeter and about two millimeters.

App. No. 10/608,725
Amdt. Dated May 26, 2006
Reply to Office Action of February 28, 2006
Atty. Dkt. No. 9129-109

33. (Canceled) A headrest assembly according to claim 25, wherein each one of said sensors is disposed at a spacing distance of greater than about one millimeter.

34. (Canceled) A headrest assembly according to claim 25, wherein each one of said sensors is a superconducting gradiometer having a pick-up coil diameter of between about four millimeters and about eight millimeters.

35. (Canceled) A headrest assembly according to claim 34, wherein said pick-up coil diameter of between about five millimeters and about seven millimeters.

36. (Canceled) A headrest assembly according to claim 35, wherein said pick-up diameter is about six millimeters.

37. (Canceled) A method of magnetoencephalography for the brain of a head of a patient, comprising: supporting the head on a headrest assembly including a headrest mounted on a portable cart having an array of magnetic sensors forming a part of an inverted SQUID dewar; supporting the body of the patient on a bed mounted on the cart; detecting electrical activity of the brain of the patient; predicting the noise in the array of magnetic sensors using a plurality of reference sensors; and subtracting the predicted noise from the electrical activity to allow use in an unshielded room.

38. (Canceled) A method according to claim 37, further including moving the headrest and the sensors relative to one another to positionally adjusting them.